

MATERIAL SAFETY DATA SHEET
ENDIT

Page : 1

SLUYTER COMPANY LTD.

375 Steelcase Road East
Markham, Ontario L3R 1G3 Canada
Tel (905) 475-6011 Fax (905) 475-3119

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER-----SLUYTER COMPANY LTD.
375 Steelcase Road East
Markham, Ontario L3R 1G3
Canada
Tel (905) 475-6011
PRODUCT NAME-----ENDIT.
PRODUCT USES-----Deodorizer and odour counteractant.
CHEMICAL FAMILY-----Alcohol based blend.

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS / %	CAS / TLV	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
ISOPROPYL ALCOHOL 30 - 60	67-63-0 400 ppm	5045 mg/kg Oral (Rat)	16000 ppm 4 Hours Inhalation (Rat)
PROPYLENE GLYCOL 7 - 13	57-55-6 100 ppm	21000 mg/kg Oral (Rat)	Not Available

SECTION 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:-----
SKIN CONTACT-----Can cause moderate skin irritation,
defatting and dermatitis.
SKIN ABSORPTION-----Not applicable.
INHALATION-----As described below.
INHALATION CHRONIC-----Nose and throat irritation.
INGESTION-----May cause headache, nausea, vomiting and weakness.
EYE CONTACT-----Irritant. Causes corneal damage.
EFFECTS OF ACUTE EXPOSURE-----Refer to "ROUTE ENTRY" section.
EFFECTS OF CHRONIC EXPOSURE-----May cause damage to the central nervous
system. May cause nausea, headache,
dizziness and drowsiness.

SECTION 04: FIRST AID MEASURES

EYE CONTACT-----Check for and remove any contact lenses.
Immediately flush with water for a minimum
of 20 minutes and get medical attention.
SKIN CONTACT-----Remove contaminated clothing. Wash
affected area with water and soap. Seek
medical attention if irritation occurs or persists.
INHALATION-----Remove patient to fresh air. If not
breathing, trained personnel should
administer artificial respiration. Get
medical attention.
INGESTION-----Dilute with large quantities of water or
milk. Do NOT induce vomiting. Get immediate
medical attention.
ADDITIONAL INFORMATION-----Contact your local poison control centre.

Ref: 0000317E

Preparation Date : May.07.2015

EMERGENCY - CALL CANUTEC (613) 996-6666 (Collect)

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY-----Flammable.
 UNDER WHAT CONDITIONS-----Combustible product. May ignite if exposed to sources of heat, sparks, open flames or temperatures above the flash point.
 SPECIAL PROCEDURES-----Self contained breathing apparatus and protective clothing is required for fire fighting personnel. Use water spray to cool fire exposed surfaces and to protect personnel.
 FLASH POINT (METHOD)-----14°C TAG Closed Cup.
 AUTO IGNITION TEMPERATURE-----350°C.
 UPPER FLAMMABLE LIMIT (% VOL)-----12.00.
 LOWER FLAMMABLE LIMIT (% VOL)-----11.60.
 EXTINGUISHING MEDIA-----Alcohol foam, CO2 or dry chemical.
 HAZARDOUS COMBUSTION PRODUCTS-----Oxides of Carbon (CO and CO2).
 SENSITIVITY TO MECHANICAL-----Not available.
 IMPACT
 SENSITIVITY TO STATIC-----Not available.
 DISCHARGE

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL-----Remove all sources of ignition, open flames, sparks and heaters. mall spills can be wiped. large spills must be collected for disposal. se a non-combustible absorbent inorganic material. Prevent run-off into drains, sewers and other waterways.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES-----Do NOT handle near any flammable materials. Avoid skin and eye contact. Maintain a good personal hygiene.
 STORAGE NEEDS-----Store away from oxidizing materials and all sources of ignition,. Store in a cool and well-ventilated area.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:-----
 EYE/TYPE-----Safety glasses.
 RESPIRATORY/TYPE-----Use NIOSH/MSHA approved respirator if the TLV is exceeded.
 GLOVES/ TYPE-----Wear impervious gloves (Neoprene or Rubber).
 CLOTHING/TYPE-----Wear adequate protective clothing.
 FOOTWEAR/TYPE-----Safety boots as specified in workplace regulations.
 OTHER/TYPE-----Eye bath and safety shower.
 VENTILATION REQUIREMENTS-----Natural ventilation is satisfactory for normal use.

SECTION 14: TRANSPORT INFORMATION

T.D.G. CLASSIFICATION-----Alcohol Exempt.

SECTION 15: REGULATORY INFORMATION

CPR COMPLIANCE-----This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS CLASSIFICATION-----Class B Div.2 Class D Div.2 Subdiv.B.

SECTION 16: OTHER INFORMATION

IMPORTANT:-----The information on this Material Safety Data Sheet is furnished without warranty, expressed or implied. All the information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations for the accuracy or sufficiency.