

MATERIAL SAFETY DATA SHEET
SUPERSLIP SILICONE (Bulk)

Page : 1

SLUYTER COMPANY LTD.

375 Steelcase Road East
Markham, Ontario L3R 1G3 Canada
Tel (905) 475-6011 Fax (905) 475-3119

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER-----SLUYTER COMPANY LTD.
375 Steelcase Road East
Markham, Ontario L3R 1G3
Canada
Tel (905) 475-6011
PRODUCT NAME-----SUPERSLIP SILICONE.
PRODUCT USES-----Silicone lubricant and release agent.
CHEMICAL FAMILY-----Silicone Solvent Blend.

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS / %	CAS / TLV	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
HEPTANE			
60 - 95	142-82-5 400 ppm	>15 mg/kg Oral (Rat)	Not Available
POLYDIMETHYLSILOXANE			
4 - 8	63148-62-9 Not Available	Not Available	Not Available

SECTION 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:-----
SKIN CONTACT-----Can cause moderate skin irritation,
defatting and dermatitis.
SKIN ABSORPTION-----Not available.
INHALATION CHRONIC-----Breathing of high vapour concentrations
could cause dizziness, headache or even
unconsciousness. May be anesthetic which
could result in other central nervous
system effects.
INHALATION-----See "EFFECTS OF CHRONIC EXPOSURE", below.
INGESTION-----Can cause gastro-intestinal irritation,
nausea, vomiting and diarrhea. Small
amounts of liquid aspirated into
respiratory system could cause severe
health effects (e.g. Bronchopneumonia or Pulmonary Edema).
EYE CONTACT-----Contains materials that are moderately
irritating to the eyes.
EFFECTS OF ACUTE EXPOSURE-----Refer to "ROUTE ENTRY" section.
EFFECTS OF CHRONIC EXPOSURE-----Prolonged or repeated skin contact may
cause drying or cracking of the
skin. Product is believed to have low
toxicity for other chronic exposures.

SECTION 04: FIRST AID MEASURES

EYE CONTACT-----Check for and remove any contact lenses.
Immediately flush with water for a minimum
of 20 minutes and get medical attention.
SKIN CONTACT-----Remove contaminated clothing. Wash
affected area with water and soap. Seek

Ref: 0000212E/B

Preparation Date : May.07.2015

EMERGENCY - CALL CANUTEC (613) 996-6666 (Collect)

MATERIAL SAFETY DATA SHEET
SUPERSLIP SILICONE (Bulk)

Page : 2

medical attention if irritation occurs or persists.
INHALATION-----Remove patient to fresh air. If not breathing, trained personnel should administer artificial respiration. Get medical attention.
INGESTION-----Do NOT induce vomiting. Get immediate medical attention.
ADDITIONAL INFORMATION-----Contact your local poison control centre.

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY-----Flammable.
UNDER WHAT CONDITIONS-----Flammable liquid. Fire hazard when exposed to heat, flame or temperatures above the flash point. Vapours are heavier than air and may travel to a source of ignition and flash-back.
SPECIAL PROCEDURES-----A self-contained breathing apparatus is required for fire fighting personnel. Use water spray to cool fire exposed surfaces and to protect personnel.
FLASH POINT (METHOD)----- -5°C TAG Closed Cup.
AUTO IGNITION TEMPERATURE----- >200°C
UPPER FLAMMABLE LIMIT (% VOL)-----6.80.
LOWER FLAMMABLE LIMIT (% VOL)-----0.60.
EXTINGUISHING MEDIA-----Alcohol foam, CO2 or dry chemical.
HAZARDOUS COMBUSTION PRODUCTS-----Oxides of Carbon (CO and CO2). Toxic fumes.
SENSITIVITY TO MECHANICAL-----Not available.
IMPACT
SENSITIVITY TO STATIC-----Not available.
DISCHARGE

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL-----Ventilate. Eliminate all sources of ignition. wear protective gear (See SECTION 8). Small spills can be wiped. Large spills must be collected for disposal. Use a non-combustible absorbent inorganic material. Prevent run-off into drains, sewers and other waterways. CAUTION: Surfaces may be slippery after use, clean thoroughly with a mineral spirits based cleaner.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES-----Do NOT place container in hot water. Avoid skin and eye contact. Avoid breathing vapours. Use adequate ventilation. Keep away from heat, sparks and open flame.
STORAGE NEEDS-----Store in a cool area, away from all sources of heat and ignition. Store in a dry, well ventilated area. Do NOT store above 49°C.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:-----
EYE/TYPE-----Safety glasses.
RESPIRATORY/TYPE-----If used indoors on a continuous basis or

MATERIAL SAFETY DATA SHEET
SUPERSLIP SILICONE (Bulk)

if the TLV is exceeded, the use of a cartridge type respirator (NIOSH/MSHA approved) is recommended.

GLOVES/ TYPE-----Not applicable.

CLOTHING/TYPE-----Wear adequate protective clothing.

FOOTWEAR/TYPE-----Safety boots as specified in workplace regulations.

OTHER/TYPE-----Eye bath and safety shower.

VENTILATION REQUIREMENTS-----Natural or mechanical (Explosion Proof) ventilation to keep vapour levels well below the TLV.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE-----Liquid.
ODOUR-----Solvent odour.
SPECIFIC GRAVITY-----0.70 - 0.80.
ODOUR THRESHOLD (ppm)-----Not available.
VAPOUR PRESSURE-----115 mmHg @ 38°C.
VAPOUR DENSITY (AIR=1)----- > 1.00.
EVAPORATION RATE-----Not available.
BOILING POINT (deg C)-----95°C - 100°C.
pH-----Not applicable.
SOLUBILITY IN WATER (% W/W)-----Negligible.
COEFFICIENT OF WATER\OIL-----Not available.
DISTRIBUTION
FREEZING POINT----- < 0°C.
MELTING POINT (deg C)-----Not applicable.
MOLECULAR WEIGHT-----Not applicable.

SECTION 10: STABILITY AND REACTIVITY

INCOMPATIBILITY-----Strong acids and strong bases. Oxidizing agents.
REACTIVITY CONDITIONS-----Excessive heat, sparks and open flame.
HAZARDOUS PRODUCTS OF-----Oxides of Carbon (CO and CO2). Toxic
DECOMPOSITION fumes. Smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL-----See "HAZARDOUS INGREDIENTS" in SECTION 2.
IRRITANCY OF MATERIAL-----Moderate.
SENSITIZING CAPABILITY OF-----Not available.
MATERIAL
CARCINOGENICITY OF MATERIAL-----No information is available and no adverse carcinogenic effects are anticipated.
TERATOGENICITY-----No information is available and no adverse teratogenicity effects are anticipated.
MUTAGENICITY-----No information is available and no adverse mutagenicity effects are anticipated.
REPRODUCTIVE EFFECTS-----No information is available and no adverse reproductive effects are anticipated.
SYNERGISTIC MATERIALS-----Not available.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL-----Not available. Can be dangerous if allowed to enter drinking water intakes. Product has an unaesthetic appearance and can be a nuisance. Do not contaminate domestic or irrigation water supplies, lakes, streams, ponds and rivers.

MATERIAL SAFETY DATA SHEET
SUPERSLIP SILICONE (Bulk)

Page : 4

BIODEGRADABILITY-----Not available. The solvent portion of this product is biodegradable and vaporizes rapidly.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL-----To be disposed of in accordance with current Local, Provincial and Federal regulations. Prevent run-off into drains, sewers and other water-ways. Consult an expert in hazardous waste for proper disposal.

SECTION 14: TRANSPORT INFORMATION

T.D.G. CLASSIFICATION----- In containers up to 1 litre - shipped as CONSUMER COMMODITY. If the shipment exceeds 500 kg in weight, shipped as CONSUMER COMMODITY - HEPTANES SOLUTION) CLASS 3.

In containers over 1 litre - HEPTANES (SOLUTION) CLASS 3
UN1206 P.G. II.

SECTION 15: REGULATORY INFORMATION

CPR COMPLIANCE-----This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.
WHMIS CLASSIFICATION-----Class B Div.2 Flammable Liquid, Class D Div.2 Subdiv B.

SECTION 16: OTHER INFORMATION

IMPORTANT:-----The information on this Material Safety Data Sheet is furnished without warranty, expressed or implied. All the information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations for the accuracy or sufficiency.