

## STICK-UM

### PRODUCT DESCRIPTION

Stick-Um is a high performance neoprene based Contact Cement for repairing leather footwear, purses and other leather items, including the installation of rubber and vinyl cove base. Outstanding properties include rapid strength build-up, plus excellent resistance to aging, weathering and moisture.



### SPECIAL FEATURES

- ◆ Long Open Time
- ◆ Strong Permanent Bond
- ◆ Easy Application
- ◆ Fast tack adhesion and good tearing strength
- ◆ Final bonds are strong, long lasting.

### TYPICAL PROPERTIES

APPEARANCE:	Light Beige
BASE:	Neoprene Rubber
DRY TIME:	10 – 20 minutes depending on temperature and surface condition
BOND STRENGTH:	400 psi in tensile shear
NON VOLATILES:	22%
FLAMMABILITY:	Extremely Flammable. Store and use under controlled conditions
ODOUR:	Strong solvent smell. Use in well ventilated areas
SOLVENTS:	Hydrocarbon and Petroleum Distillates blend
SPECIFIC GRAVITY:	0.80 – 0.85
VISCOSITY:	1500 to 1700 cps @ 20°C
COVERAGE:	4 – 7 sq. metres per litre depending on application method and core porosity.
SHELF LIFE:	Approximately twelve months at 20°C in unopened containers
VOC INFORMATION:	This product emits VOC's (volatile organic compounds) in its use. Always ensure that the use of this product complies with local VOC Emission Regulations, where they exist. <u>The VOC level is 411 grams/litre (SCAQMD Test Method 316A)</u>

**IMPORTANT:** -As this product can be used to bond a variety of substrates in numerous applications, it is recommended that you test the suitability of this product prior to use for your application.