


PVC S40-LV SOLVENT CEMENT

Regular Body PVC Solvent Cement – CLEAR (LOW VOC)

PRODUCT DESCRIPTION

PVC S40-LV (Clear) is a regular bodied cements for PVC joints with interference fits only. Fast setting. Recommended for welding PVC Electrical Conduit and Duct systems creating a solid waterproof joint. Used with our approved 3 PRIMER or 3V PRIMER. Meets with the ASTM D-2564 Standard of approval and CSA Certified.



DIRECTIONS FOR USE

Applying the Cement will require the use of Primer and following the step-by-step procedure for cutting the pipe and preparing the surfaces. These procedures are set out in detail on the Cement and Primer container labels.

PACKAGING

The S40-LV range of PVC Solvent cements are packaged in a variety of metal container sizes and types, which include the screw top cans with an applicator dauber attached.

SAFETY DATA

It is extremely important to read the relevant safety data in the WHMIS section of the label and the relevant Material Safety Data Sheet, before using the product.

TYPICAL PROPERTIES

APPEARANCE:	Clear light bodied liquid
VISCOSITY RANGE:	205 - 215 cps at 23°C
FLAMMABILITY:	Extremely flammable
ODOUR:	Strong Ketone Odour. Use in well-ventilated areas
SOLVENTS:	Tetrahydrofuran, Methyl Ethyl Ketone (MEK) and Acetone
SPECIFIC GRAVITY:	0.90 to 1.00
FREEZING POINT:	<0°C
SHELF LIFE:	Approximately twelve months in tightly closed containers
FLASH POINT:	- 5°C TAG Closed Cup
VOC INFORMATION:	This product emits VOC's (volatile organic compounds) in its use. Always ensure that the use of this product complies with local VOC Emission Regulations, were they exist. <u>The VOC level is 475 grams/litre (SCAQMD Test Method 316A)</u>
LEED® COMPLIANT:	Meets LEED® credit requirements for Low VOC emitting materials EQ Credit 4 Table 2.

